

Black-start by off-shore wind turbines

Wind Turbine – Converter Interaction PROMOTioN WP3

Dr Ömer Göksu, DTU Wind Energy, Prof R. Blasco-Gimenez (Universitat Politecnica de Valencia –Spain)
28 February 2019, PROMOTioN MIGRATE Joint Workshop, Berlin



© PROMOTioN – Progress on Meshed HVDC Offshore Transmission Networks
This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 691714.

WP3 Partners



Technical University of Denmark



UNIVERSITAT
POLITÈCNICA
DE VALÈNCIA



DNV·GL



RWTHAACHEN
UNIVERSITY



ENERGINET

ABB

SIEMENS

Ørsted

equinor 



© PROMOTiON – Progress on Meshed HVDC Offshore Transmission Networks

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 681744

11.10.2018



© TenneT TSO GmbH

- Diode Rectifier as offshore HVDC
- Grid Forming Wind Turbines
- Offshore AC Grid Start-up
- Black Start by Offshore Wind Turbines
- Conclusions




© PROMOTioN – Progress on Meshed HVDC Offshore Transmission Networks

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 691714.

03.05.16


3

Diode Rectifier Units as offshore HVDC




Key features of the Modular Diode Rectifier Unit

- Encapsulated, rugged equipment
- Bio degradable and flame retardant insulation
- Simple and robust power electronics
- Small platform with easy transport and installation
- High reliability, minimal maintenance
- No offshore DC converter as single point of failure
- Flexible offshore installation options due to modular rectifier concept



© Siemens AG 2016 All rights reserved.



© Siemens AG 2016 All rights reserved.

Source: Siemens AG




© PROMOTiON – Progress on Meshed HVDC Offshore Transmission Networks


This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 691714.

04-03-2019


Offshore AC Grid Start-up Options




Umbilical AC Cable



Nearby VSC-HVDC (or AC)



Local Energy Storage (e.g. battery, diesel)



Black-startable wind turbines

Black Start by Offshore Wind Turbines

Objective:

To avoid issues of non-operating wind turbines;


- Moisture
- Icing
- Vibrations
- Deformation

Objective:

To energize WPP and substations' auxiliary w/o any external supply

Objective:

To provide black start for the onshore power system




- Wind turbines will start w/o grid voltage
- Wind turbines will supply themselves using wind (houseload operation)

WPP will energize up to the onshore PoC


WPP will operate similar to the conventional black start units



Control capability evolution



- Wind Turbine self-start
- Wind Power Plant Islanded Operation
- Black/brown start (HVAC and/or HVDC)
- Improvement of system stability in large systems with reduced or zero synchronous generation
- Improved HVDC integration
 - HVDC diode rectifier
 - LCC-HVDC rectifier stations
 - VSC-HVDC rectifier stations



thejapantimes
NEWS

北海道

Hokkaido industries still struggling following quake-triggered blackout

JkAl

Key industries in Hokkaido are still struggling with secondary damage from the massive blackout triggered by the powerful earthquake a month ago.

The power outage even forced factories far away from the seismic center of the 6.7 magnitude earthquake to suspend operations.

Food and beverage factories and retailers had to dispose of products as refrigerators stopped working, suffering larger damage from the secondary effects than the direct impact of the earthquake.

Dairy and livestock farmers have yet to see production return to predisaster levels due to severe aftereffects of the blackout.

"It will take time to restore production to levels before the disaster," an official of the Hokuren Federation of Agricultural Cooperatives in Hokkaido said.

According to the federation, the amount of raw milk it collected from group farmers in early September fell 16 percent from a year earlier. Although raw milk production started recovering in mid-September, many farmers are still suffering from the impact of the blackout, which made them unable to use milk pumps and caused their cows to develop mastitis.

Furthermore, farmers had no choice but to dispose of produced raw milk because they were unable to cool it for storage.

The Hokkaido Prefectural Government estimated damage from the earthquake on its dairy and livestock industry at some ¥2.4 billion as of Friday.

A Toyota Motor Corp. subsidiary was forced to suspend transmission

OCT 6, 2018

ARTICLE HISTORY

PRINT  SHARE


PHOTOS

🔍 [CLICK TO ENLARGE](#)



KEYWORDS

EARTHQUAKE, TOYOTA
HOKKAIDO, ELECTRICIT



Motivation

Japan Wind Energy Association

Huge earthquake damaged 3 coal fired power plants (Tomatou-azuma power plant, 165MW in total) at about 3am on 6 Sep..

They produced about half of Hokkaido's power demand at that time.

Sudden loss of huge power supply caused frequency decrease, then remaining power plants (including wind farms) stopped one after another.


Hokkaido island has gone "black out". 303 wind turbines of 358MW at 61 sites were forced to shut down.

It needed about 40 hours to re-start whole island-wide grid system.


100MW of wind turbines & battery systems restarted 52 hours later from shut down.

The rest of wind turbines restarted 126 - 130 hours later.

Some delay was needed to secure the grid stability.



Black start operation (HVAC)








Source: energinet.dk

PROMOTiON WP3 ◦ WTG – Converter Interaction









rblasco@upv.es 12

Results



Results





Aeroelastic-EMT co-simulation

40 MW block load

Grid forming power	48MW	96MW	192MW
Gearbox extreme load	0.6 pu	0.25 pu	0.125 pu
Minimum wind speed	10.6 m/s	8.7 m/s	6.9 m/s




Fault Recovery

HVAC connection


PROMOTiON WP3 ◦ WTG – Converter Interaction

50 x 8MW islanded Wind Power Plant

100% Grid Forming Converters



20% load



80% load



© PROMOTiON – Progress on Meshed HVDC Offshore Transmission Networks

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 691714.

rblasco@upv.es 16

- **Grid Forming Wind Power Plants allow for additional applications and functionality.**
 - **Improved HVDC Integration (DRU, MMC-HVDC)**
 - **Islanded operation**
 - **Black start / service restoration operation**
- **Different technical solutions are available and not all functionality requires grid forming capability**
- **Adequate control coordination can help to reduce the amount of grid forming power required for a particular application**
- **Fault recovery is very important with a large number of grid forming WTGs/WPPs, particularly if both grid forming and grid following WTGs/WPPs are considered**




Next steps

- Requirements for HVAC/HVDC black/brown start operation
- Specification of benchmark scenarios and test cases
- Specification of controller validation by simulation
- Validation of controllers
- Validation in a realistic scenario (North Jutland, replicate black start from Skagerrak HVDC)
- D3.7 : Report with the compliance evaluation results using simulations (late 2019)
- D3.8 : List of requirement recommendations to adapt and extent existing grid codes (late 2019)



Next Steps

- **CHIL validation** (WP16 demonstrators - DNV-GL, RWTH Aachen, UPV)
 - DRU connected grid forming wind power plants
 - Black start for HVAC connected wind power plants
 - Black start for HVDC connected wind power plants
 - HVDC grid connected WPPs



APPENDIX

DISCLAIMER & PARTNERS

COPYRIGHT

PROMOTioN – Progress on Meshed HVDC Offshore Transmission Networks

MAIL info@promotion-offshore.net WEB www.promotion-offshore.net

The opinions in this presentation are those of the author and do not commit in any way the European Commission

PROJECT COORDINATOR

DNV GL Netherlands B.V.

Utrechtseweg 310, 6812 AR Arnhem, The Netherlands

Tel +31 26 3 56 9111

Web www.dnvgl.com/energy

CONTACT

PARTNERS

DNV GL Netherlands B.V., ABB AB, KU Leuven, KTH Royal Institute of Technology, EirGrid plc, SuperGrid Institute, Deutsche WindGuard GmbH, Mitsubishi Electric Europe B.V., Affärsverket Svenska kraftnät, Alstom Grid UK Ltd (Trading as GE Grid Solutions), University of Aberdeen, Réseau de Transport d'Électricité, Technische Universiteit Delft, Equinor ASA, TenneT TSO B.V., Stiftung OFFSHORE-WINDENERGIE, Siemens AG, Danmarks Tekniske Universitet, Rheinisch-Westfälische Technische Hochschule Aachen, Universitat Politècnica de València, SCiBreak AB, Forschungsgemeinschaft für Elektrische Anlagen und Stromwirtschaft e.V., Ørsted Wind Power A/S, The Carbon Trust, Tractebel Engineering S.A., European University Institute, S.A., European Association of the Electricity Transmission & Distribution Equipment and Services Industry, University of Strathclyde, S.L., Prysmian, Rijksuniversiteit Groningen, MHI Vestas Offshore Wind AS, Energinet.dk, Scottish Hydro Electric Transmission plc, SCiBreak AB



© PROMOTioN – Progress on Meshed HVDC Offshore Transmission Networks

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 691714.

03.05.16

20