


The background of the slide is a photograph of an offshore wind farm. Several wind turbines are visible in the distance, their white towers and blades standing against a blue sky and sea. The water is a deep blue with some whitecaps. The overall tone is professional and related to renewable energy.

IMPACT OF HARMONICS ON FUTURE CONVERTER DOMINATED POWER SYSTEM

Joint MIGRATE & PROMOTioN workshop


Berlin, 28th February 2019

Name: Dr. Blaž Kirn


Company: ELES

E-Mail: Blaz.Kirn@Eles.si

WHY IS POWER QUALITY A CENTRAL ISSUE TO SUCCEED IN MASSIVE POWER ELECTRONIC INTEGRATION?



WP5 – Power quality in transmission networks with high PE penetration





Partners: UNIMAN, TUB, UL, EIMV, TalTech, ELES, TenneT, EIRGRID, SPEN, ELERING

POWER QUALITY PHENOMENA RELATED TO PE

- Voltage dips and Temporary Over-Voltage
- Harmonic distortion (PE harmonic injections, device susceptibility to voltage harmonics, grid resonance, poor controllers performance causing excessive harmonic distortion)
- Supraharmonics
- Flicker and voltage fluctuation
- Harmonic resonance
- Voltage Unbalance
- Voltage variation
- Frequency variation
- Frequency fluctuations

Main focus of WP5




PE DEVICES EMT MODELS

Models developed for:

- + High voltage direct current system (**HVDC**),
- + Static compensator (**STATCOM**),
- + Static-var compensator (**SVC**),
- + Wind-turbine generators (**WTG type 3 and 4**),
- + Solar photovoltaics (**PV**) and
- + Battery storages (**BS**).


- For each device, three types of models with different level of detail and complexity have been developed: the electromagnetic transient (**EMT**) model, the **average RMS** model and the **harmonic load-flow** model (frequency domain).



PE DEVICES EMT MODELS

A **representative topology** for each PE device (amongst a wide variety of different topologies and implementations currently available) has been selected. This approach has been adopted in order to provide a **generic**, yet **representative**, model and more importantly, to **propose a methodology** for EMT modelling of PE devices for PQ studies.

Harmonic loadflow models developed by “scanning” the EMT models in various operating points.



PROPAGATION OF PQ DISTURBANCES IN THE GRID


TYPE: Frequency variations

Harmonic distortion


DEVICE MODEL: Average RMS model

Harmonic Load Flow model


**TESTING
NETWORK:**




MERRA wind data



Irish grid




IEEE 68 bus network



10 minutes simulation with wind data in DIgSILENT PowerFactory

Varying SNSP from 60% to 90%





Harmonic load flow based on Monte Carlo simulation of harmonic emissions



60% SNSP

90% SNSP



Frequency:





Balancing
power of
synchronous
generators:




Voltage:



- Fourier analysis of frequency variations due to intermittent supply of wind farms indicates that the main impact is on primary regulation, not inertia of the system.
- Primary regulation balancing energy almost doubles going from 60% to 90% SNSP
- Voltage variations minimum due to voltage control functionality in PE converters





- Focus is on smoothing the frequency pattern by preserving as much renewable energy generation as possible
- Modularity of design (N-1, independent as well as coordinated operation)
- Applying a modified power reference synthesizer block in wind turbine control
- Adding short term wind speed as well as frequency forecast (up to 1 minute)





60% - 90% SNSP

4 load (non)linearity cases



THD:
(220 kV)



THD:
(110 kV)




- Approximately three time increase of average THD from 60% to 90% PE.
- 110 kV is affected the most – in 90% PE, almost 5% of busses exceeds 3% 95th THD
- Load (non)linearity has great impact on harmonics – for the case of 70% SNSP, increasing the share for non-linear load of distribution networks from 20% to 50% leads to doubling the average THD.




- Cases: Ref., 1,2,3 -> 60%, 70%, 80,%, 90% SNSP


Ireland Voltage THD
60% wind THDu 95%





Ireland Voltage THD
70% wind THDu 95%



Ireland Voltage THD
80% wind THDu 95%




Ireland Voltage THD
90% wind THDu 95%




95th percentile of voltage THD 60% - 90% SNSP


Ireland Voltage Harmonics
90% wind 5th harmonic




Ireland Voltage Harmonics
90% wind 7th harmonic



Ireland Voltage Harmonics
90% wind 11th harmonic





Ireland Voltage Harmonics
90% wind 13th harmonic



95th percentile of voltage harmonics (5th, 7th, 11th, 13th) 60% - 90% SNSP

- Methodology will be implemented in IEEE 68 bus network
- Creating a probabilistic case study of one year data varying load (non)linearity, location and quantity of FACTS and PE (wind, solar) devices to achieve 60% to 90% SNSP
- Based on harmonic distortion results, mitigation points in the network will be proposed for each SNSP



- Methodology of harmonic distortion mitigation for network and device based solution
- CBA based analysis: mitigation with the following parameters: location, number, type and size of mitigation devices (passive / active (part of other devices) filters, active filters at the PE devices)
- CBA based analysis: cost of mitigation vs financial and technical benefit (sensitivity analysis)




Fig. 3. Heatmaps of $UBPIs$ obtained with the application of 10 solutions with and without mitigation.




Fig. 2. Convergence curves of various components against the number of mitigation solutions applied.

ADDED VALUE FOR STAKEHOLDERS

- Overview of existing and future PQ issues in transmission networks and identification of main sources for PQ issues (T5.1, D5.1).
- Methodology for the assessment of the Influence of PQ Disturbance on Operation of PE Rich Power Networks is proposed in line with the developed scenarios in MIGRATE project WP1 (T5.3/T5.4)
- Mitigation techniques for PQ disturbances will be proposed, techniques include device based solutions (passive and control) in order to improve the level of PQ in the transmission networks. (T5.5)
- PQ phenomena Visualisation tool developed (T5.3)
- Understanding of PMU applicability for PQ monitoring (T5.3)

The background of the slide is a photograph of an offshore wind farm. Several wind turbines are visible in the distance, their white towers and blades standing against a dark, overcast sky. The water is a deep blue with visible ripples. In the foreground, there are large, semi-transparent, light blue geometric shapes: a parallelogram on the left, a parallelogram on the right, and a large 'X' shape at the bottom, all partially overlapping the text and the background image.

THANK YOU FOR YOUR
ATTENTION!



elering



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 691800.



The information, documentation and figures in this presentation are written by the MIGRATE project consortium under EC grant agreement No 691800 and do not necessarily reflect the views of the European Commission. The European Commission is not liable for any use that may be made of the information contained herein.